

EAN 5 905 167 875 216

Product number

15825400000002487

SECURA HEAT VINYL CLICK

Material XPS

Description

Insulating material for the acoustic use under floating floors

LVT

Technical Parameters

Symbol	Parameter	Value		Class	Unit	Norm
T	Thickness	5	+/- 0,40	[-]	[mm]	EN 823:2013
L	Length	1200	-1% +5%	[-]	[mm]	EN 822:2013
W	Width	600	-1% +2,5%	[-]	[mm]	EN 822:2013
Q	Squareness	<5		[-]	[mm/m]	EN 824:2013
S	Flatness	<2		[-]	[mm/m]	EN 825:2013
AW	Surface mass	0,2	+/- 15%	[-]	[kg/m ²]	EN ISO 23997:2012
RWS	Reflected walking sound	62	+/- 2	[-]	[sone]	EN 16205:2021
IS	Impact sound improvement	18	+/- 2	[-]	[dB]	EN ISO 10140:2021
CS	Compressive strength at 0.5 mm compression	500	+/- 10%	CS3	[kPa]	EN 826:2013
CC	Static compressive strength	25	+/- 10%	CC2	[kPa]	EN 1606:2013
DL	Dynamic compressive strength	> 500 000		DL3	[cycles]	EN 13793:2004
PC	punctual conformability	3	+/- 10%	PC3	[mm]	EN ISO 868:2005
TR	Thermal Resistance	0,17	+/- 10%	[-]	[m ² K/W]	EN 12664:2002
SD	sD-value	[-]		[-]	[m]	EN 12086:2013
RLB	Resistance to Large Ball	[-]		[-]	[mm]	EN 13329+A2:2022
RTF	Reaction on fire	Efl		[-]	[-]	EN 13501-1:2019

Logistic Parameters

Packaging Unit	Form	Amount +/- 10%		Weight +/- 10%		Sizes	
	Plate	5,76	[m ²]	1,18	[kg]	1200 x 600 x 40	[mm x mm x mm]
Collective packaging	Form	Amount +/- 10%		Weight +/- 10%		Sizes	
	Palette	311,04	[m ²]	89,72	[kg]	1200 x 800 x 1950	[mm x mm x mm]
Packaging materials	Amount of Paper +/- 10%		Amount of Foils +/- 10%		Amount Remaining +/- 10%		
	0,12 [kg]		0,03 [kg]		[-] [kg]		
Other	Customs tariff number		Waste key		Recycling		
	39211100		170604		Yes		

Standards and Certificates

EN 16354:2018

The information is based on the current state of knowledge and technological development. The information may not contain comprehensive data and all previous versions of the technical data sheet are no longer valid.

Please send questions to the following email address: Reklamacje@decora.pl

creation date

2023-08-18

modification date

2023-08-18

Printed

21.02.2024 14:31